JZUKI KING QU

Winch Mount

Kit Components:		
Item#	Qty.	Description
1	1	Winch Mount
2	1	Hardware Kit (HK-001)
2.1	4	5/16"-18 x 1.00 Hex Flange Bolt
2.2	4	5/16"-18 Hex Flange Nylock Nut

<u>INSTALLATION INSTRUCTIONS</u> **Note:** Make sure all hardware needed to complete this mount is in the package. Thoroughly read through and understand the instructions before installing.

- 1. Attach the Hawse or roller fairlead (not included) to the front of the mount using the hardware provided with your winch kit or roller fairlead.
- 2. Install the winch mount plate in the mounting location as shown in the exploded view using the provided 5/16" hardware.
- 3. Insert the winch (not included) into the mounting location
- 4. Install the winch to the mount using the hardware provided with your winch.
- 5. Your electrical contactor goes under the seat in any avalable location.

Note: On older machines, the plastic is already predrilled. There will be 4 rubber plugs in the holes just behind your tool kit. You will have trouble getting the screws in unless you lift the plastic a bit. It's best to run the bolts up from the bottom, nuts on top.

- 6. Under the dash pod there are 3 bullet connectors. The orange one is a switched hot lead to use with your switch.
- 7. Run the winch power wires in the pre-ran plastic tubing (A) on the RH side of your machine.
- 8. Using the instructions provided with your winch, wire accordingly.

PART #100450







