

SUZUKI KING QUAD

Winch Mount

PART #100450

Kit Components:

| Item # | Qty. | Description |
|--------|------|---------------------------------|
| 1 | 1 | Winch Mount |
| 2 | 1 | Hardware Kit (HK-001) |
| 2.1 | 4 | 5/16"-18 x 1.00 Hex Flange Bolt |
| 2.2 | 4 | 5/16"-18 Hex Flange Nylock Nut |

INSTALLATION INSTRUCTIONS

Note: Make sure all hardware needed to complete this mount is in the package. Thoroughly read through and understand the instructions before installing.

1. Attach the Hawse or roller fairlead (not included) to the front of the mount using the hardware provided with your winch kit or roller fairlead.
2. Install the winch mount plate in the mounting location as shown in the exploded view using the provided 5/16" hardware.
3. Insert the winch (not included) into the mounting location
4. Install the winch to the mount using the hardware provided with your winch.
5. Your electrical contactor goes under the seat in any available location.

Note: On older machines, the plastic is already pre-drilled. There will be 4 rubber plugs in the holes just behind your tool kit. You will have trouble getting the screws in unless you lift the plastic a bit. It's best to run the bolts up from the bottom, nuts on top.

6. Under the dash pod there are 3 bullet connectors. The orange one is a switched hot lead to use with your switch.
7. Run the winch power wires in the pre-ran plastic tubing (A) on the RH side of your machine.
8. Using the instructions provided with your winch, wire accordingly.

