

SXS TRANS

HIGH PERFORMANCE TRANSMISSION OIL

DESCRIPTION:

Mineral-based transmission fluid formulated specifically for use in modern side-by-side (SXS) vehicles. Robust formulation maintains film thickness and viscosity stability across all operating temperatures to minimize chain and gear wear. Advanced formula ensures optimal clutch engagement, preventing slippage and facilitating smooth shifts even under extreme loads. Exceeds the requirements of JASO MA2.

FEATURES & BENEFITS:

- Formulated for use in modern side-by-side (SXS) transmissions
- Can also be used in SXS wet rear brake systems
- Shear-stable formula minimizes gear wear while preventing pitting and spalling
- Ensures optimal clutch engagement, prevents slippage and facilitates smooth shifts
- Robust additive system protects against rust and corrosion for extended usage
- Exceeds JASO MA2 specifications

APPLICATIONS:

For modern SXS transmissions. Not designed for hypoid-type gear cases. Can be used in SXS wet rear brake systems.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	80 WT
APPEARANCE	VISUAL	Amber
VISCOSITY @ 40°C (cSt)	D445	71.1
VISCOSITY @ 100°C (cSt)	D445	9.9
VISCOSITY INDEX	D2270	121
FLASH POINT (°C)	D92	246
POUR POINT (°C)	D97	-39
DENSITY @ 15 °C (g/ml)	D4052	0.868