



SXS SYNTHETIC ENGINE

100% SYNTHETIC, ESTER-FORTIFIED 4-STROKE ENGINE OIL

DESCRIPTION:

Full synthetic, ester-fortified 4-stroke engine oil specifically formulated for side-by-side (SXS) engines. Synthetic, oxidatively-stable formulation combines surface-active esters with a shear-stable polymer system to provide excellent film thickness and viscosity stability across all operating temperatures. Advanced, proprietary additive system reduces temperatures and increases power output while keeping your engine running clean, trouble-free and extending the life of the machine. Exceeds the requirements of API SN PLUS / JASO MA2.

FEATURES & BENEFITS:

- Recommended for all OEM equipment
- Formulated specifically for SXS engines
- Superior protection and oxidative stability at any temperature
- Reduces temperature and increases power output
- Shear-stable, ester-fortified formula maintains oil viscosity and film thickness
- Surface-active chemistry aggressively attaches to engine surfaces and keeps them clean
- Exceeds API SN PLUS and JASO MA2 specifications

APPLICATIONS:

For all air and water-cooled SXS 4-stroke gasoline engines.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	0W-40	5W-40	5W-50	10W-50
APPEARANCE	VISUAL	Amber	Amber	Amber	Amber
VISCOSITY @ 40°C (cSt)	D445	78.2	84.7	112.7	127.9
VISCOSITY @ 100°C (cSt)	D445	13.6	13.8	19.0	18.5
VISCOSITY INDEX	D2270	178	168	190	163
FLASH POINT (°C)	D92	222	242	249	222
POUR POINT (°C)	D97	-54	-48	-45	-42
DENSITY @ 15 °C (g/ml)	D4052	0.847	0.851	0.854	0.856

EXPERIENCE THE DIFFERENCE**Made In The USA**